

Hygienic Sprayer



Installation Instructions

1. Turn off the wall valve that supplies water to the toilet tank (pic #1). Empty the toilet tank by flushing it and place a cloth or dish under the tank to catch any remaining water.



2. Disconnect the hose that connects the water supply to the toilet tank. (pic #2).



3. Attach the "shut off valve connector" to the bottom of the tank. Be sure to place the rubber washer inside the "shut-off valve connector" (pic #3).



4. Connect the water supply hose to the bottom of the "shut off valve connector" (pic #4).



5. Connect Hygienic Sprayer metal hose to the side of the "shut off valve connector" (pic #5). Be sure that the rubber washer is inside the diaper sprayer metal hose connector.



6. Connect the sprayer head to the Hygienic Sprayer metal hose. Attach the clip bracket to the toilet tank and hang the new Hygienic Sprayer (pic #6).

7. Turn back on the wall valve that supplies water to the toilet (pic #1).

INSTRUCTIONS FOR USE:

Take the SP-2, turn on the Shut Off valve connector, direct the hand held bidet where you want to use it, and press the water pressure lever.

WARNING: YOU MUST TURN OFF THE VALVE AFTER EACH USE

Failure to turn off after every use, may weaken the flexible hose. Manufacturer is not responsible for damage which may be caused by failure to follow this recommendation.